KERNOW COATINGS

KERNOWJET™
LATEX & SOLVENT

Supreme 500

KernowJet Supreme 500 is a New Generation Composite Textured Pop-Up display film, compatible with HP Latex, Eco-Solvent and UV inkjet systems. Suitable for indoor and outdoor use.

Property	Typical Value	Unit	Test Method
Total Thickness	495 +/- 10	µ	Electronic micrometer
Weight	660 +/- 15	gsm	Internal method
Gloss 60°	6 +/- 2	%	BYK Gardner
Opacity	>99	%	TAPPI T519
CIE Whiteness Index	>100	CIE WI	ISO 11475

- Innovative, textured, light-block Pop Up display film
- Highly stable, resists heat & stays flat
- Anti-slip coating – accurate reliable printing

Compatibility Guidance

Mild Solvent	Eco Solvent	Latex
✓✓✓	✓✓✓	✓✓✓

Recommended Conditions

Printroom	15°C - 30°C	30% - 65% RH
Usage	-40°C – 60°C	10% - 90% RH
Storage	10°C - 20°C	20% - 50% RH

Available in widths of: 914mm, 1067mm, 1270mm and 1524mm

Version: EU 16/06

Kernow Coatings Ltd
Kernick Road
Penryn, Cornwall
TR10 9DQ

www.kernowcoatings.com
sales@kernowcoatings.com
T: +44 (0)1326373147
F: +44(0)1326376614

Registered in England
No. 1092182
A Member of the Sensitisers
Group of Companies

The information provided herein is correct to the best of our knowledge. No liability for any errors, facts or opinions is accepted. We recommend users make their own assessments to satisfy themselves as to the suitability of this product for their application.

Copyright Sensitisers Group 2016