WALL & CEILING

# NON-WOVEN DESIGN2WALL UV 150

matt 2500, 150 g/m$^2$

Economical non-woven wallpaper with a natural surface

The Non-woven design2wall UV 150 matt is an uncoated non-woven wallpaper for inkjet printing with latex and UV inks. This product is suitable for digital printing of wall decorations and wallpapers. It has a matt finished, natural surface and can be pasted without further surface protection, with standard non-woven wallpaper paste. It is flame retardant and certified.

## Technologies

LAT UV

## Properties

## Advantages

- High wet and dry strength
- Dry strippable
- PVC free
- FSC® certified
- Flame retardant and C-s1, d0 certified according to European Standard EN 13501-1
- Hang using standard non-woven wallpaper paste

OEKO-TEX® CONFIDENCE IN TEXTILES STANDARD 100 D15-0796 HOHENSTEIN HTTI Tested for harmful substances. www.oeko-tex.com/standard100

FSC www.fsc.org FSC® C005732 The mark of responsible forestry

## General tips

To maintain the high quality of this wallpaper, it should be stored and converted in a climate of 30 – 65 % relative humidity and at a temperature of 10 – 30 °C (50 – 86 °F).

## Physical data

| Name | Value | Norm |
|---|---|---|
| Weight [g/m²] | 150 | ISO 536 |
| Thickness (paper) [µm] | 320 | ISO 534 |
| ISO Brightness [%] | 88 | ISO 2470-1 |
| Opacity [%] | 90 | ISO 2471 |
| Tensile strength MD [N/15mm] | 148 | ISO 1924-3/2/300 |
| Tensile strength CD [N/15mm] | 94 | ISO 1924-3/2/300 |
| Wet tensile strength MD [N/15mm] | 47 | ISO 3781 |
| Wet elongation CD (Fenchel) [%] | 0.1 | A 10-011/27 |
| Water absorbency (Cobb) [g/m²] | 18 | ISO 535 |