



Window Film

## GLASSAPEEL WHITE

GLASSAPEEL WHITE is a window film that utilizes hybrid micro gelsuction cupped technology.

### SUMMARY

- 1. Unique adhesive force**
  - No glue residue / Reusable / Washable / Non-expert installation
- 2. Blocks the light**
  - 100% blockout
- 3. No wrinkles**
  - Surface wrinkles do not appear even after countless uses
- 4. Super fast drying of solvent inks**
  - Two times faster than other PP media

### SPECIFICATION

|                             |                                       |
|-----------------------------|---------------------------------------|
| Base Material<br>Surface    | Polypropylene Block out<br>Semi-Matte |
| Base Caliper (Adh included) | 175 $\mu$ m $\pm$ 5                   |
| Liner Caliper (Pet)         | 50 $\mu$ m $\pm$ 5                    |
| Total Caliper               | 225 $\mu$ m $\pm$ 10                  |
| Base Weight (GSM)           | 180gsm $\pm$ 10                       |
| Liner Weight (GSM)          | 75gsm $\pm$ 10                        |
| Total Weight (GSM)          | 255gsm $\pm$ 20                       |
| Width                       | 60", 54", 50", 42", 30"               |
| Length                      | 30m (100ft)                           |
| Core                        | 3"                                    |

### COMPATIBILITY

INK compatibility  
Solvent, Eco-solvent, Mild-solvent, Latex, UV, Offset

Printer compatibility  
Most solvent, Latex, UV, and offset printing systems

### APPLICATION

- Windows, glass, plexiglass, and metals, or any surface as smooth as glass
- Retail shop decoration, museum decoration, art center decoration, office interior, home deco, architecture market, private spaces, sliding windows, glass partitions, etc.

### NOTE

|                     |                                                             |
|---------------------|-------------------------------------------------------------|
| Printing conditions | 15~30°C (59~86°F)<br>Humidity 30~60%                        |
| Storage             | Stored at 10~25°C (50~77°F)<br>Humidity 50~55% RH           |
| Shelf Life          | 1 year stored in original package<br>under above conditions |

*The above data is based on tests by our own efforts according to international standards. Above data can be changed as the case may be without any prior notification. No media warranty is implied. This specification sheet shall be used only within the purpose of its defined usage and also shall not be copied without the approval of Maker.*

